

# EUROPEAN PATENT OFFICE

## Patent Abstracts of Japan

PUBLICATION NUMBER : 11283668  
PUBLICATION DATE : 15-10-99

APPLICATION DATE : 30-03-98  
APPLICATION NUMBER : 10083778

APPLICANT : SANYO ELECTRIC CO LTD;

INVENTOR : TAKAHASHI MASATOSHI;

INT.CL. : H01M 10/40 H01M 2/02 H01M 4/02 H01M 4/58

TITLE : LITHIUM ION BATTERY

ABSTRACT : PROBLEM TO BE SOLVED: To suppress the generation of gas in a battery and to minimize the expansion of the battery by using mixed lithium salt of lithium salt and  $\text{LiPF}_6$  as the solute of an electrolyte, and specifying the ratio of  $\text{LiPF}_6$ .

SOLUTION: An exterior body made of metal aluminum or an aluminum alloy and having the thickness of 0.4 mm or below is provided. A positive electrode using a lithium-containing composite oxide ( $\text{LiCoO}_2$  or the like) as a positive electrode material, a negative electrode using a carbon material (graphite) having the (d) value ( $d_{002}$ ) of  $3.40 \text{ \AA}$  or below on the lattice plane (002) as a negative electrode material, and an electrolyte made of a solvent and a solute are stored in the exterior body to form a lithium ion battery. Mixed lithium salt of the lithium salt  $[\text{LiN}(\text{C}_2\text{F}_5\text{SO}_2)_2]$  expressed by formula  $\text{LiN}(\text{C}_n\text{F}_{2n+1}\text{SO}_2)_2$  and  $\text{LiPF}_6$  is used for the solute of the electrolyte, where (n) is an integer of 2 or above, and the ratio of  $\text{LiPF}_6$  in the mixed lithium salt is set to 20 mole % or below.

COPYRIGHT: (C)1999,JPO